



Composite Impact Wrench

(Twin Hammer)



TP0414

1/2" Composite Air Impact Wrench

MAX. TORQUE IN REVERSE: 780 ft/lb (1054Nm)

OPERATED BY TURN KNOB IN 3-FORWARD & 2-REVERSE

Net Weight: 2.1 Kgs w/ Handle Exhaust

MODEL No.	Square Drive	MAX Torque		MAX Torque in Reverse	Free Speed RPM	Air Inlet	Hose Size	Net Weight		Overall Length		Packing (Kgs) Pcs/Ctn/NW/GW/Cuft
		Ft/lb	N-m					lbs	kgs	in.	mm.	
TP0414	1/2"	600	810	780 ft/lb (1054Nm)	8,000	1/4"	3/8"	4.6	2.1	7.4"	187	10/CTN/21/24/1.5'



Composite Impact Wrench

(Twin Hammer)



FORWARD / REVERSE PUSH-BUTTONS DESIGN

4 POSITION POWER SETTING BY TURN KNOB

TP0438

3/8" Composite Air Impact Wrench

MAX. TORQUE IN REVERSE: 450 ft/lb (607Nm)

Net Weight: 1.38 Kgs w/ Handle Exhaust

TP0421

1/2" Mini Composite Air Impact Wrench

MAX. TORQUE IN REVERSE: 500 ft/lb (678Nm)

Net Weight: 1.38 Kgs w/ Handle Exhaust

TP0340

1/2" Composite Air Impact Wrench

MAX. TORQUE IN REVERSE: 780 ft/lb (1054Nm)

Net Weight: 2.2 Kgs w/ Handle Exhaust

TP0434

3/4" Composite Air Impact Wrench

MAX. TORQUE : 1350 ft/lb (1830Nm)

Net Weight: 3.4 Kgs w/ Handle Exhaust

MODEL No.	Square Drive	MAX Torque		MAX Torque in Reverse	Free Speed RPM	Air Inlet	Hose Size	Net Weight		Overall Length		Packing (Kgs) Pcs/Ctn/NW/GW/Cuft
		Ft/lb	N-m					lbs	kgs	in.	mm.	
TP0438	3/8"	400	542	450 ft/lb (607Nm)	11,000	1/4"	3/8"	3	1.38	6.1"	155	10/CTN/17/18/1.1'
TP0421	1/2"	400	542	500 ft/lb (678Nm)	11,000	1/4"	3/8"	3	1.38	6.1"	155	10/CTN/17/18/1.1'
TP0340	1/2"	600	810	780 ft/lb (1054Nm)	8,000	1/4"	3/8"	4.84	2.2	7.3"	186	10/CTN/22.5/24.5/1.5'
TP0434	3/4"	900	1220	1350 ft/lb (1830Nm)	7,000	3/8"	1/2"	7.48	3.4	8.47"	215	4/CTN/17.5/19/1.2'